

Addendum - VI

Ref.: Plg/165/RFID/11936:

E-Tender No.KoPT/Kolkata Dock System/PnR/4/17-18/ET/219

Following amendments are issued for the RFID based access control system project tender:

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment																																				
1	RFP Annexure II – Technical Specifications	As per technical specification mentioned in the RFP published on 11-08-2017	Modify	<p>Revised Technical Specifications:</p> <p>1. Port Access Control System (PACS)</p> <table border="1" data-bbox="846 730 1980 1396"> <thead> <tr> <th data-bbox="846 730 936 810">Sl.No</th> <th data-bbox="936 730 1720 810">Minimum specification/ functionality required</th> <th data-bbox="1720 730 1854 810">Compliance</th> <th data-bbox="1854 730 1980 810">Remarks</th> </tr> </thead> <tbody> <tr> <td colspan="4" data-bbox="846 810 1980 906">Mandatory compliance (These are the mandatory requirements. Bidder will be disqualified if he fail to comply with these requirements)</td> </tr> <tr> <td data-bbox="846 906 936 1034">1</td> <td data-bbox="936 906 1720 1034">The RFID solution software shall be developed/ customized, installed, supported and maintained by the service provider</td> <td data-bbox="1720 906 1854 1034"></td> <td data-bbox="1854 906 1980 1034"></td> </tr> <tr> <td colspan="4" data-bbox="846 1034 1980 1074">A. Port officer Authorization Module</td> </tr> <tr> <td data-bbox="846 1074 936 1153">2</td> <td data-bbox="936 1074 1720 1153">Provision to admin access into the complete system by a Port Authority</td> <td data-bbox="1720 1074 1854 1153"></td> <td data-bbox="1854 1074 1980 1153"></td> </tr> <tr> <td data-bbox="846 1153 936 1201">3</td> <td data-bbox="936 1153 1720 1201">Provision to Audit every pass issued</td> <td data-bbox="1720 1153 1854 1201"></td> <td data-bbox="1854 1153 1980 1201"></td> </tr> <tr> <td data-bbox="846 1201 936 1281">4</td> <td data-bbox="936 1201 1720 1281">Provision to restrict pass issue permission by Port Supervisor/ Scrutinizer</td> <td data-bbox="1720 1201 1854 1281"></td> <td data-bbox="1854 1201 1980 1281"></td> </tr> <tr> <td data-bbox="846 1281 936 1361">5</td> <td data-bbox="936 1281 1720 1361">Provision to restrict number of passes per Company by a Port Authority</td> <td data-bbox="1720 1281 1854 1361"></td> <td data-bbox="1854 1281 1980 1361"></td> </tr> <tr> <td data-bbox="846 1361 936 1396">6</td> <td data-bbox="936 1361 1720 1396">Direct access to all software & database by authorized</td> <td data-bbox="1720 1361 1854 1396"></td> <td data-bbox="1854 1361 1980 1396"></td> </tr> </tbody> </table>	Sl.No	Minimum specification/ functionality required	Compliance	Remarks	Mandatory compliance (These are the mandatory requirements. Bidder will be disqualified if he fail to comply with these requirements)				1	The RFID solution software shall be developed/ customized, installed, supported and maintained by the service provider			A. Port officer Authorization Module				2	Provision to admin access into the complete system by a Port Authority			3	Provision to Audit every pass issued			4	Provision to restrict pass issue permission by Port Supervisor/ Scrutinizer			5	Provision to restrict number of passes per Company by a Port Authority			6	Direct access to all software & database by authorized		
Sl.No	Minimum specification/ functionality required	Compliance	Remarks																																					
Mandatory compliance (These are the mandatory requirements. Bidder will be disqualified if he fail to comply with these requirements)																																								
1	The RFID solution software shall be developed/ customized, installed, supported and maintained by the service provider																																							
A. Port officer Authorization Module																																								
2	Provision to admin access into the complete system by a Port Authority																																							
3	Provision to Audit every pass issued																																							
4	Provision to restrict pass issue permission by Port Supervisor/ Scrutinizer																																							
5	Provision to restrict number of passes per Company by a Port Authority																																							
6	Direct access to all software & database by authorized																																							

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment			
					Port Authority		
				7	Provision to limited access to Port Supervisor/Scrutinizers at the Gates		
				8	Provision to scan activity of pass issue by each operator at any counter		
				9	Provision to get summary report of all activities by operators on shift wise, daily, weekly, & monthly basis		
				10	Provision to log all activities of logged in operators issuing the passes		
				B. Sponsoring Company Registration has			
				11	Provision to define company type		
				12	Provision to register a company under one company type		
				13	Provision to define category and it rules		
				14	Provision to register one or more category under one Company		
				15	Revision to define validity based on the license date, bank guarantee date, and documents expiry date and categories validity period		
				16	Provision to define companies without any basic validity		
				17	Provision for Pre-renewal		
				18	Provision for renewal after expiry of registration		

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment				
				19	Provision for extension of validity for Company- Category and Category on the basis of validity Provision for parameterized, Dynamic definition Provision to declare defaulter and or blacklist a category and or a company immediately or with future date			
				20	Provision to declare defaulter and or blacklist all the permits under the category and or Company automatically due to default/blacklist of Company or category			
				21	Provision to restore the Company and or Category separately or together along with their Permits			
				22	Provision to cancel the Company/Company- Category as per rules			
				23	Provision to define Maximum Validity period for the type of permit of any Category in Category Master			
				24	Provision for not allowing cancellation without cancelling all permits under it or if the company is defaulted or blacklisted			
				25	Provision for forcible Cancellation of a Company			
				26	Provision to cancel all the permits under it automatically			
				27	Provision to declare quota for various types of Permits and provision to increase/decrease quota permanently, daily or for a specific period.			

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment				
				28	Provision to maintain the list of authorized signatories under company-category with Photo and Signature			
				29	Provision to maintain the list of Director/Partners/Proprietors with their photo and signature			
				30	Provision to define the Issuing Authority for different types of Permits.			
				31	User authentication should be based on OTP on the registered mobile including user-id and password			
				C. Authenticated User Enrolment and Issuance of permits has				
				32	Provision to enroll User – Employee biometrics, identification details, photograph.			
				33	Provision to attach Scanned documents.			
				34	Provision to generate uniqueness for every User			
				35	Provision to retrieve information based on Biometrics, User Identification details			
				36	Provision to verify User credentials like biometrics etc before issuing the Permit			
				37	Provision to issue User permit till the Company-Category's Validity date, Document Validity date, Maximum validity period			
				38	Provision to Generate, Print Permit on Smart Card, Water proof sticker, Paper			
				39	Provision to link Smart card / RFID tag/ paper pass with			

S. No.	RFP volume and clause	Existing clause	Change type (New/ Modify/ Delete)	Revised clause/ Amendment					
					Users credentials				
				40	Provision to renew / issue duplicate permits				
				41	Provision to blacklist or restore a user permit				
				42	Provision to record IN / OUT movement of User / vehicle / Employee				
				43	Provision to issue permits for different span of time like daily, weekly, Monthly, Quarterly, yearly				
				44	Provision to issue permits to a group or to every member of group individually				
				45	Provision to limit access of pass holder to specific areas				
				46	Provision to declare defaulter and or blacklist a user				
				47	Provision to restore defaulter and or blacklisted user				
				48	Provision to display Users Photograph on the LCD when moving in or out of the gate				
				49	Provision to push data of defaulters and or blacklisted user on all the readers. Thus controlling access of black listed persons				
				50	For out entry Flap barrier to be operated physically/ automated				
				51	Provision for various parameterized reports. User can generate their own MIS				
				52	Provision for customizable forms for storing user data along with photo identification, finger prints				

S. No.	RFP volume and clause	Existing clause	Change type (New/ Modify/ Delete)	Revised clause/ Amendment				
				53	Maintaining unique data of Users from which passes isto be generated quickly			
				D. Authenticated Vehicle Enrolment and issuance of Vehicle Permit features				
				54	Provision to enroll Vehicle			
				55	Provision to Link passengers with Vehicle			
				56	Provision to generate Vehicle permits for different time period like Quarterly / yearly, Daily			
				57	Provision to renew / issue Duplicate Vehicle permit			
				58	Provision to change the Owner of the Vehicle			
				59	Track the IN /OUT movement of Vehicle at gate through RFID tag			
				60	Provision to limit access of vehicle to specific areas			
				61	Maintaining unique data of Vehicle from which passes is to be generated quickly			
				62	RFID based Internal Tracking of Equipment, Container, Vehicle,& Visitors within the Port premises.			
				E. Cash Collection and Remittance features				
				63	Provision to Define various permit			
				64	Provision to enter tariff for each definition of Permit.			
				65	Provision to Change Tariff for each Definition of Permit and should be applicable for a specific period			
				66	Provision to Collect Cash as per the rules defined			
				67	Provision for remittances made			

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment					
				68	Provision to collect deposit in advance against each company				
				69	Provision to collect cash against each permit as per the rules defined by making necessary withdrawal entry (Credit/Debit)				
				70	System should integrate with a Payment Gateway for remittance of fees by users as per requirement of the Port. Provision for online payment to Port Account Directly				
				71	Conveniently available Pass Collection Counters including third party such as (ICDs, CFS, e-Governance Centers, Authorized Centers, etc.)				
F. Blacklisting & Policy Enforcement Module									
				72	Provision to blacklist user, vehicle, company				
				73	Provision to auto-block pass issue to blacklisted entities				
				74	Provision to raise alert for blacklisted related requests				
				75	Provision to report suspicious or anomalous activities with severity levels				
				76	Provision to create rules defining Port Gate Entry Policy				
				77	Provision to enforce Gate Entry Policy such entry restricted from a specific gates, etc.				
				78	Provision to restrict individuals & vehicles to specific areas or zones				
				79	Provision of rules to generate alerts by email, SMS, or				

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment				
					Phone Call			
				G. User Module Features:				
				80	Hierarchy of the users maintained Levels of the users and rights given to the levels could be changed through system			
				81	Maker Checker facility for the user creation			
				82	Log of creation of User, User Validity, password Validity, and Password Policy maintained			
				83	Copy / Paste not allowed in the login / Password Fields			
				84	Validation in such a way that no compromise by SQL Injection Techniques Password encrypted			
				85	Last login Date/time stored in the system and displayed on the screen to the user			
				86	Enforcement of the initial default password and forcing the user to change password after certain No. of days parameterized			
				87	After certain no. of attempts the user gets locked and the no. of attempts parameterized			
				88	Disabling the user automatically after certain period parameterized if the login is not at all used			
				89	Facility to disable the user manually			
				90	History of login details to the user of their own login & of all users for administrator / Super User login			

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment				
				91	System should be secured enough for preventing of unauthorized attempts for access over web and security should be based on Cert-In guidelines			
				H. RFID Card Management Module				
				92	Advance enrolment of the port sponsor companies, users, vehicles, etc.			
				93	Pre-personalization and Personalization of cards			
				94	Printing of cards & stickers			
				95	Management of Temporary users			
				96	Provision to Issue Passes from authorized locations outside the Port			
				97	Remote disabling of cards			
				98	Alerting on expired card usage attempts Security & data encryption in card or server end			
				I. Comprehensive MIS Reports & Integration Module				
				99	Provision for Dashboard to view the current status of traffic at the Port			
				100	Tracking of each and every individual, vehicle, visitor across Port area			
				101	Category based reporting of traffic inside as well as at the gates			
				102	Classification of Users by pass type, usage activities, access zones			
				103	Classification of Vehicles by pass type, usage activities,			

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment					
					access zones				
				104	Report on Vehicles associated by Drivers & Cleaners				
				105	Report of pass issued in by day, week, month, year, as well as by gates.				
				106	Graphical view of all the reports summary				
				107	Detailed report pass issue activities by Gate, by Period, by Operator				
				108	Summarized report of pass issue activities by Gate, by Period, by Operator				
				109	Reports providing anomalous activities at the gate				
				110	Report providing time spent by each and every man & vehicle				
				111	Report providing areas visited by individuals & vehicles				
				112	Report detailing overstay by individuals & vehicles				
				113	Report detailing additional movement by Individuals & Vehicles beyond a defined threshold				
				114	Report classifying internal and external vehicle movements				
				115	Report on pass payment collections and reconciliation				
				116	Provision to check complete details of vehicle or individual on handheld System				
				117	Provision to transfer data to Port servers on real-time or scheduled basis				
J. Gate Interface Module									

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment				
				118	Gate Barrier Interface Module			
				119	Flap barrier Interface Module			
				120	License Plate Capture Camera Integration Module			
				121	Display Unit Controller			
				122	AVI Interface Module			
				123	User Photo Capture Interface Module			
				124	Container Reader & 3D Capture Interface Modules			
				125	Handheld Terminal for Mobile Spot Checking as well as speedy movement at the gates			
				K. Control Room & 24/7 Monitoring				
				126	Summarized dashboard			
				127	Real-time Data updates and Visuals			
				128	Anomaly & Policy Break Reporting			
				L. Backup, Archival & Retrieval Management				
				129	Backup server for record keeping			
				130	Regular synchronization with front-end server			
				131	Historical data keeping for audit trail			
				132	Fallback server			
				133	Doubles up as load balancing server			
				134	Distributed Architecture			
				135	High Availability Master Database			
				136	Archival & Retrieval System			
				137	Backup & DR			

S. No.	RFP volume and clause	Existing clause	Change type (New/ Modify/ Delete)	Revised clause/ Amendment			
				M. Policy Framework & Rules Engine			
				138	Configurable policy framework and rules engine		
				139	Simplified Approval System with Email, SMS, & Mobile alerts to Scrutinizer		
				N. Integration APIs			
				140	System should support integration or data exchanges with legacy or future systems as per requirement of Port. 3 level comprehensive APIs to connect to various existing & future integrations		
				141	XML & Web service based open interfaces		
				O. Biometric Aadhaar Integration			
				142	RFID Pass should be linked to Aadhaar biometrics		
				143	Handheld based spot checking with Aadhaar database		
				144	All the parameters of Biometric Devices for Authentication should be as per certification of UIDAI as per latest STQC Scheme for certification of UIDAI Biometric Devices (Authentication)		
				P. Kiosk Module			
				145	RFID Pass renewal through standalone remote kiosk		
				146	Ability to make payment using kiosk		
				147	Provision to update & renew card using kiosk		
				148	Provision to spit slip of acknowledgement		
				149	Provision to remote health monitor the kiosk		
				150	Provision for information dispersal through kiosk		

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment			
				Q. Equipment & Asset Tracking Module			
				151	Provision to get real-time visibility of assets & equipment in the port premises under surveillance		
				152	Provision to identify asset or equipment on a 2D or 3D layout		
				153	Provision to track assets & equipment over longer distances		
				154	Provision to track multiple assets with conflict resolution		
				155	Provision to search all, one, or many assets on a single screen		
				156	Provision to search by individual attribute or entire set of attribute		
				157	Provision to save search results on a CSV, Excel, PDF, Print, or Copy		
				158	Multi-paging of results		
				159	Dashboard of summary of assets & equipment and their status		
				160	Provision to add, delete, edit assets & equipment		
				161	Provision to add unlimited features to an asset or equipment		
				162	Provision for bulk import & export		
				163	Provision to assign assets to department, person, role, etc.		

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment				
				164	Provision for individual user to login and check the status of the assets assigned to them			
				165	Provision to request for asset assignment, return, repair, etc.			
				166	Provision of Comprehensive asset & equipment lifecycle management			
				R. Image Processing				
				167	Offline comparison of man, material images captured by cameras			
				168	Alerts when images are not consistent			
				169	Comparative results and anomaly reports			
				2. Database				
				Sl.No	Minimum specification/ functionality required	Compliance	Remarks	
				1	Highly performance reliable database with uptime			
				2	High availability with redundancy & clustering			
				3	Should support existing system & IT security rules and processes			
				4	Should also support OS security services			
				5	Database replication & migration should be real time without affecting the operations			

S. No.	RFP volume and clause	Existing clause	Change type (New/ Modify/ Delete)	Revised clause/ Amendment				
				6	The database should be highly scalable and should sustain incremental & peak loads over the operation period			
				7	Minimum 300 concurrent user connections support			
				8	Performance should not degrade with significant incremental data each day			
				9	Should be able to support both Windows & Linux			
				10	Should support audit trail and policy compliance of sensitive data			
				11	Should support periodic & occasion backup and restore without having to hold the operations			
				12	Both incremental & full back up to be supported			
				13	Should have inbuilt alert mechanism to warn potential issues			
				14	Crash recover mechanisms to be supported.			
				15	Should be able to distribute data onto physical storage devices for record keeping			
				16	Should support offline DB setup and quick search for record keeping			
				17	Relational Database Management System			
					Make: MySQL/ MSSQL/ Oracle/ Sybase/ PostgreSQL			
				3. RFID HF reader				

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment			
				Minimum specification/ functionality required	Compliance	Remarks	
				Operating frequency	13.56 Mhz		
				Connectivity/ Communication	Ethernet, PROFINET/ Modbus/TCP		
				Read range	Min. 2-3"		
				Support	Supports multiple technologies (standard iCLASS, MIFARE and MIFARE DESFire EV1)		
				Protocols/ Standards	ISO 15693, ISO 18000-3, ISO 14443 Type A/B		
				Operating temperature	-35°C to 65°C		
				Humidity	5-95% Non-condensing		
				Indications	Buzzer, LED indications for access granted, access denied, etc.		
				Regulations	CE/ FCC/ UL/ RoHS		
				Power	5-16 V DC, PoE		
				Features	<ul style="list-style-type: none"> - Encrypted data transfer between card and reader - Should have latest authentication, communication and security standards/ protocols - 802.1X authentication 		

S. No.	RFP volume and clause	Existing clause	Change type (New/ Modify/ Delete)	Revised clause/ Amendment				
				Protection	IP 65			
				Make	Make: HID/ Bosch/ Schneider Electric/ Siemens/ Lenel			
				4. RFID UHF reader				
				Minimum specification/ functionality required			Compliance	Remarks
				Operating frequency	860-960 MHz			
				Connectivity/ Communication	Ethernet			
				Connectivity options	TCP/IP, Wiegand, RS232/485			
				Read range	5-12 meters, Min. 80-100 cards/ second			
				Antenna type	Inbuilt, Circular Polarization Antenna			
				External control	2 × GPO and 2 × GPI			
				Protocols/ Standards	ISO18000-6C, EPC UHF Class 1 Gen 2, Dense reader mode			
				Protection	IP 68 else, if lesser rating like IP 52/ 53, then to be supplied with proper protection casing for protection against dust and water			
				Operating temperature	-35°C to 65°C			

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment				
				Humidity	5-95% Non-condensing			
				Power	12 Volt DC supply, POE			
				Indications	Buzzer, LED indications for access granted, access denied, etc.			
				Regulations	CE/ FCC/ UL/ RoHS			
				Support	Should support: - Industrial protocols like PROFIBUS/ PROFINET/ TCP/IP/ EtherNet/IP			
				Make	Make: ThingMagic/ Convergence Systems Ltd./ Impinj/ Feig			
				5. UHF RFID card				
				Minimum specification/ functionality required			Compliance	Remarks
				Protocols/ standards	EPC Class1 Gen2, ISO 18000-6C, ISO/IEC-7810-2002 compliant			
				Frequency	860 - 960 MHz			
				Read range	Between 2 to 10 meters			
				Memory	512 bit user memory			
				Dimension	As per ISO standards			
				Temperature	-20 °C to 60 °C			
				Humidity	98% non-condensing			

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment			
				Features	Data retention: 100,000 cycles		
					Card should support secure authentication methods and protocols, latest cryptographic standards		
					Card shall be interoperable, based on open standards and not subject to any patents/ proprietary standards		
					Waterproof, Dust proof, IP 68		
					White printable surface, external ID number, should be compatible to direct to card printing and thermal printing		
				Data retention	Minimum 10 years		
				Make	Make: HID/ Bosch/ Coresonant/ Schneider Electric/ Seimens		
				6. HF RFID card			
				Minimum specification/ functionality required		Compliance	Remarks
				Protocols	ISO 15693 for tracking, ISO/IEC 14443A and ISO/IEC 14443 for MiFARE and ISO 18000-3		
				Frequency	Operating frequency - 13.56 Mhz		
				Read range	Between 3-12"		
				Memory	Minimum 1024 bits of memory		

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment			
				Dimension	As per ISO standards		
				Temperature	Operating Temperature: Between -20 to +70 degrees Celsius		
				Humidity	Humidity: 5% to 95% (non-condensing)		
				Features	Card should support secure authentication methods and protocols, latest cryptographic standards		
					Card shall be interoperable, based on open standards and not subject to any patents/ proprietary standards		
					Waterproof, Dust proof, IP 68		
					White printable surface, external ID number, should be compatible to direct to card printing and thermal printing		
				Data retention	Minimum 10 years		
				Make	Make: HID/ Bosch/ Coresonant/ Schneider Electric/ Seimens		
				7. Handheld Terminal			
				Minimum specification/ functionality required		Compliance	Remarks
				Operations: Integrated operations for both HF & UHF operations			
				Read Range : HF - min. 5 cms, UHF - min. 75-100 cms			

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment		
				Read Rate : Min 50 tags / second		
				Protocol: ISO 15693, ISO18000-6C, EPC UHF Class 1 Gen 2 with optional Dense Reader Mode (Class 3 Gen 2 compliant)		
				Antenna: Circularly polarized		
				User Interface – Input: QWERTY keyboard, Touch Screen, Trigger Button		
				User Interface – Output: LCD, LEDs, Buzzer		
				Connectivity : Wi-Fi (802.11 b/g), USB, GPRS, Ethernet, Bluetooth		
				Memory slot: SD Card, Standard SD and SDHC		
				Battery: Lithium Polymer 2200 mAh or higher battery pack (Rechargeable) with battery charger kit		
				Weight : Maximum 1 Kg		
				IP: IP 54		
				Make: ThingMagic/ Convergence Systems Ltd./ Impinj/ Feig		
				8. Smartcard printer		
				Minimum specification/ functionality required	Compliance	Remarks
				Printing specifications : Direct-To-Card printer with Dual-sided printing		
				Features : a. 100 card feeder		

S. No.	RFP volume and clause	Existing clause	Change type (New/ Modify/ Delete)	Revised clause/ Amendment			
				b. 30 card capacity output hopper			
				c. Single card feed mode			
				d. LCD control display			
				e. 300 dpi print resolution			
				f. Should support the card size being offered as part of the project along with other standard industry card sizes			
				Encoding module for contactless cards: MIFARE, DESFire, iCLASS/ iCLASS SE, ISO7816, ISO14443 A/B			
				Read/ Write module for contactless cards: MIFARE, DESFire, iCLASS/ iCLASS SE, ISO7816, ISO14443 A/B			
				Interfaces : Bidirectional USB 2.0 high speed or above & Ethernet			
				Color printing: Monochrome & Full Colour			
				Environmental Specifications : Printer should withstand high level of humidity and salty conditions			
				Print speed : Minimum 150 cards per hour			
				Approvals/ Certifications: As per applicable Indian Standards			
				Cleaning Kit: Should be included/ integrated by default			
				Accessories: Should be supplied with all accessories like Printer driver CD, USB cable, power cable (Indian)			
				Make: Samsung/ Zebra/ HP			

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment		
				9. RFID Reader/ Writer		
				Minimum specification/ functionality required	Compliance	Remarks
				Protocol/ Standard : Support EPCglobal Gen 2 (ISO 18000-6C) with Anti-Collision and DRM		
				Frequency: 860 to 960 MHz		
				Connectivity: USB connectivity for Laptop/ Desktop		
				Read Rate: Up to 50 tags/second		
				Read Distance: Up to 3 ft depending on tag sensitivity and orientation		
				Make: Feig/ Impinj/ ThingMagic		
				10.Data Centre and Disaster Recovery Centre		
				Minimum specification/ functionality required	Compliance	Remarks
				Modular design		
				Scalable based on future requirements		
				Should have appropriate racks for housing PACS servers, switches, storage devices with provision to scale upto a minimum of 25% of the present project infrastructure capacity		

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment			
				Sufficient Air condition, dust free environment and fire detection and suppression			
				Temperature and Humidity sensors			
				Connectivity & structured cabling			
				Fixtures such as plumbing and lighting as required			
				Security cameras, card readers, restricted and controlled access			
				Adequate redundancy measures for equipment, power, data, etc.			
				Partitioning as required			
				False ceiling as required			
				Fire rated doors and paintings			
				11.Port Server			
				Minimum specification/ functionality required		Compliance	Remarks
				Description	High availability server solution with single socket 8 core or higher		
				Processor	Intel Xeon processor E5-2620v4,2.1 GHz, 15MB Cache (per processor), Intel Hyper-threading technology		
				Memory	128 GB Memory, expandable to 256 GB		

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment				
				Drive bays	8* 2.5" SAS Drive bay hot pluggable with complete redundancy			
				Hard drives	2*1.2 TB 10K RPM SAS Disks. Should be redundant and should support 200GB SSD for future expansion			
				Optical Drive	DVD-RW			
				Expansion slots	Built in 2* PCI-express – Should be redundant, Hot pluggable			
				Graphics	One VGA port			
				Network	Usable 2 X 10/100/1000 Ethernet ports. Both ports should be redundant			
				I/O Ports& Connectors	Pluggable. 1* Active service network modem, 1*10/100 Management port 4 USB port, 2* 9 Pin serial port			
				Input device	USB or PS2 Keyboard and mouse			
				Power Supply	Hot plug and redundant power supply (230V @ 50Hz) unit			
				Power Cord	230 V @50Hz, Indian power cords to be supplied			
				Operating System	Microsoft windows 2008 or latest (Should be able to install in the same machine quoted). Pre-installed from OEM			
				Software	System management software to monitor system health at local console and over network.			

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment				
				Other requirements	The server should have hardened drivers for OS and protect the system from transient errors.			
					The server should offer minimum 99.999%			
					Should be able to install Microsoft windows, Linux, VM Ware on the same machine quoted/supplied			
					Server should mandatorily be able to connect to all leading external storage seamlessly like IBM, HP, EMC, Netapp, Hitachi			
					Scope includes supply & installation			
					Give compliance statement for the above specifications.			
					Bidder should attach the OEM technical Literature of the proposed model with clear indication of compliance to the technical sepecifications			
					Bidder should furnish all necessary part codes including service components from OEM's (Part codes should be from OEM)			
				Support Services	Direct problem call logging with manufacturer			
					24/7 support services directly from manufacturer			
				Make	IBM/ DELL/ HP/ STRATUS/ LENOVO			

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment																																										
				<p>12.IP Camera – Gates</p> <table border="1"> <thead> <tr> <th data-bbox="848 550 1720 630">Minimum specification/ functionality required</th> <th data-bbox="1720 550 1848 630">Compliance</th> <th data-bbox="1848 550 1960 630">Remarks</th> </tr> </thead> <tbody> <tr> <td data-bbox="848 630 1720 678">Camera type : Fixed Bullet IP Camera</td> <td data-bbox="1720 630 1848 678"></td> <td data-bbox="1848 630 1960 678"></td> </tr> <tr> <td data-bbox="848 678 1720 726">Image sensors : 1 / 2.8 “ mm progressive scan CMOS</td> <td data-bbox="1720 678 1848 726"></td> <td data-bbox="1848 678 1960 726"></td> </tr> <tr> <td data-bbox="848 726 1720 774">Resolution : 2 Megapixel-60 fps in 1920 x 1080</td> <td data-bbox="1720 726 1848 774"></td> <td data-bbox="1848 726 1960 774"></td> </tr> <tr> <td data-bbox="848 774 1720 821">Lens: Varifocal, f = 2.8 - 10mm power zoom lens,F1.2-1.6</td> <td data-bbox="1720 774 1848 821"></td> <td data-bbox="1848 774 1960 821"></td> </tr> <tr> <td data-bbox="848 821 1720 901">Day/night : Day and Night IR cut filter. Should give clear images/ videos in very low light conditions</td> <td data-bbox="1720 821 1848 901"></td> <td data-bbox="1848 821 1960 901"></td> </tr> <tr> <td data-bbox="848 901 1720 949">Light : 0.05 lux color and 0 lux with built-in IR</td> <td data-bbox="1720 901 1848 949"></td> <td data-bbox="1848 901 1960 949"></td> </tr> <tr> <td data-bbox="848 949 1720 997">IR distance : Built-in IR Light up to 30m</td> <td data-bbox="1720 949 1848 997"></td> <td data-bbox="1848 949 1960 997"></td> </tr> <tr> <td data-bbox="848 997 1720 1077">Video compression & streaming : H.264 (with High Profile support) / MJPEG/ MPEG-4</td> <td data-bbox="1720 997 1848 1077"></td> <td data-bbox="1848 997 1960 1077"></td> </tr> <tr> <td data-bbox="848 1077 1720 1125">WDR : 100dB</td> <td data-bbox="1720 1077 1848 1125"></td> <td data-bbox="1848 1077 1960 1125"></td> </tr> <tr> <td data-bbox="848 1125 1720 1173">Card slot : MicroSD, 32 GB card to be supplied</td> <td data-bbox="1720 1125 1848 1173"></td> <td data-bbox="1848 1125 1960 1173"></td> </tr> <tr> <td data-bbox="848 1173 1720 1220">Audio : 2-way audio with microphone input</td> <td data-bbox="1720 1173 1848 1220"></td> <td data-bbox="1848 1173 1960 1220"></td> </tr> <tr> <td data-bbox="848 1220 1720 1268">Alarm : Alarm Input and alarm output</td> <td data-bbox="1720 1220 1848 1268"></td> <td data-bbox="1848 1220 1960 1268"></td> </tr> <tr> <td data-bbox="848 1268 1720 1316">Power : 12 VDC ± 10%, PoE based on IEEE standards (802.3af)</td> <td data-bbox="1720 1268 1848 1316"></td> <td data-bbox="1848 1268 1960 1316"></td> </tr> </tbody> </table>	Minimum specification/ functionality required	Compliance	Remarks	Camera type : Fixed Bullet IP Camera			Image sensors : 1 / 2.8 “ mm progressive scan CMOS			Resolution : 2 Megapixel-60 fps in 1920 x 1080			Lens: Varifocal, f = 2.8 - 10mm power zoom lens,F1.2-1.6			Day/night : Day and Night IR cut filter. Should give clear images/ videos in very low light conditions			Light : 0.05 lux color and 0 lux with built-in IR			IR distance : Built-in IR Light up to 30m			Video compression & streaming : H.264 (with High Profile support) / MJPEG/ MPEG-4			WDR : 100dB			Card slot : MicroSD, 32 GB card to be supplied			Audio : 2-way audio with microphone input			Alarm : Alarm Input and alarm output			Power : 12 VDC ± 10%, PoE based on IEEE standards (802.3af)		
Minimum specification/ functionality required	Compliance	Remarks																																												
Camera type : Fixed Bullet IP Camera																																														
Image sensors : 1 / 2.8 “ mm progressive scan CMOS																																														
Resolution : 2 Megapixel-60 fps in 1920 x 1080																																														
Lens: Varifocal, f = 2.8 - 10mm power zoom lens,F1.2-1.6																																														
Day/night : Day and Night IR cut filter. Should give clear images/ videos in very low light conditions																																														
Light : 0.05 lux color and 0 lux with built-in IR																																														
IR distance : Built-in IR Light up to 30m																																														
Video compression & streaming : H.264 (with High Profile support) / MJPEG/ MPEG-4																																														
WDR : 100dB																																														
Card slot : MicroSD, 32 GB card to be supplied																																														
Audio : 2-way audio with microphone input																																														
Alarm : Alarm Input and alarm output																																														
Power : 12 VDC ± 10%, PoE based on IEEE standards (802.3af)																																														

S. No.	RFP volume and clause	Existing clause	Change type (New/ Modify/ Delete)	Revised clause/ Amendment			
				Mounting : Suitable for Pole and Wall mounting in Lanes			
				Recording software: To be included			
				Support: ONVIF & IPv6			
				Compatibility: Should support open API supported by other Network Video Recording softwares			
				Management: Through web interface & multi-camera management applications			
				Make: Axis/ Pelco/ Bosch/ Panasonic			
				13.Camera - Registration counter			
				Minimum specification/ functionality required	Compliance	Remarks	
				5 megapixel or above, CMOS			
				Resolution: 1920x1080			
				Auto focus lens system, Built-in flash			
				Color depth: 24 bit true color			
				Video capture: HD quality			
				Built-in microphone			
				Upto 30 fps, H.264/ MPEG-4 Advanced Video Coding			
				High speed USB			

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment				
				Make: Sony/ Canon/ Nikon/ Olympus				
				14.Camera - Pedestrian lane				
				Minimum specification/ functionality required			Compliance	Remarks
				360 degree Camera for Pedestrian lanes				
				Image Sensor	2-Megapixel progressive scan CMOS Sensor, 360° overview and panoramic views			
				Frame rate	Minimum 25 fps @ 1920x1080			
				Lens	Varifocal, P-iris Lens			
				Day and night	Removable IR-cut Filter for Day & Night Function, Built-in IR Illuminators, Effective up to minimum 30 Meters			
				Video compression & streaming	H.264/MJPEG/MPEG-4			
					WDR for Visibility in bright and dark environments			
				Audio streaming	Two-way, full duplex, Echo cancellation and noise reduction			
				Audio input & output	Built-in microphone & speaker			
				Casing	IP66 1K10 vandal resistant enclosure. Outdoor weatherproof enclosure with OEM mounting			

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment				
					arrangements			
				Power	PoE, 12VDC(±10%)			
				15.PC - For Lanes & Counters				
				Minimum specification/ functionality required			Compliance	Remarks
				Processor : Intel Core i5-3500 or equivalent or Higher, 3.3 GHz, 6MB L3 Cache				
				HD Graphics & 10/100/1000 Network : Integrated				
				Memory : 4GB 1333 MHz DDR3 RAM with 16 GB expandability				
				Hard Disk Drive : 1 TB 7200 rpm SATA HDD				
				Monitor : 47 cm (18.5 inch) TFT/LED Digital Colour Monitor TCO-05 certified.				
				Keyboard : 104 Keys or Better				
				Mouse : Optical Scroll Mouse				
				Should have: - 6 USB Ports (with at least 1 in front, minimum 2 USB 3.0) - Audio port for microphone and headphone - Minimum 2 LAN ports - Minimum 2 PCI Express slots				

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment			
				DVD Drive : DVD R/W			
				Operating System : Windows 10 Professional (64 bit) preloaded with media.			
				Make: Dell/ HP/ Lenovo/ IBM			
				16.Boom Barrier			
				Minimum specification/ functionality required		Compliance	Remarks
				Application : Outdoor			
				Barrier length: 3-6 mtrs			
				Opening/ closing time: Between 0.3-4 secs			
				Voltage: 80-264 VAC, 50/ 60 hz			
				Housing: All housing & internal parts should be with rust & corrosion free metals with suitable Epoxy coating as applicable			
				Enclosure rating: IP 54			
				Temperature: -22°F to +122°F			

S. No.	RFP volume and clause	Existing clause	Change type (New/ Modify/ Delete)	Revised clause/ Amendment			
				Features: - Integrated feature to detect vehicle presence - Boom with reflective strips - Access control operation - Automatic & manual through push button - When struck by Trailer / other equipment, barrier should have the feature to move/swing to prevent damage - Shall function with the Access control solution implemented in the premises, network, etc			
				Compliance: CE/ UL			
				Make: Magnetic AutoControl/ Elka/ Automatic Systems/ Gunnebo			
				17.Flap Barrier			
				Minimum specification/ functionality required	Compliance	Remarks	
				Application: Indoor/ Outdoor			
				Throughput: Minimum 25-30 people per minute			
				Traffic flow: Bi-directional			
				Width: Standard 520mm & Wide 900mm			
				Flaps: Retractable obstacles			
				IP: 32 and/ or 54			
				MCBF: Minimum 4-5 million cycles			

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment												
				<p>Features:</p> <ul style="list-style-type: none"> - Should be fully functional, compatible and integrable with 3rd party RFID card readers and RFID solutions - Should be fully functional and compatible with 3rd party RFID based Access Control System applications - Should prevent Tailgating, Piggybacking, Pass back through alarms - Bi-directional motorised operation - Adjustable speed - Automatic/ Configurable opening in the event of power failure and emergencies - All Housing and internal parts should be rust & corrosion free metals or alloys of high strength or with suitable epoxy coating <p>Make: Magnetic AutoControl/ Elka/ Automatic Systems/ Gunnebo</p>												
				<p>18.55" LED display</p> <table border="1" data-bbox="846 1104 1982 1359"> <thead> <tr> <th data-bbox="846 1104 1720 1189">Minimum specification/ functionality required</th> <th data-bbox="1720 1104 1848 1189">Compliance</th> <th data-bbox="1848 1104 1982 1189">Remarks</th> </tr> </thead> <tbody> <tr> <td data-bbox="846 1189 1720 1273">Type : LED, size 55" (minimum) Professional display</td> <td data-bbox="1720 1189 1848 1273"></td> <td data-bbox="1848 1189 1982 1273"></td> </tr> <tr> <td data-bbox="846 1273 1720 1359">Display Resolution : 1920 x 1080p (min) (FHD resolution)</td> <td data-bbox="1720 1273 1848 1359"></td> <td data-bbox="1848 1273 1982 1359"></td> </tr> </tbody> </table>				Minimum specification/ functionality required	Compliance	Remarks	Type : LED, size 55" (minimum) Professional display			Display Resolution : 1920 x 1080p (min) (FHD resolution)		
Minimum specification/ functionality required	Compliance	Remarks														
Type : LED, size 55" (minimum) Professional display																
Display Resolution : 1920 x 1080p (min) (FHD resolution)																

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment																																						
				<table border="1"> <tr> <td colspan="4">Connectivity : 1 x HDMI & 1 x USB</td> </tr> <tr> <td colspan="4">Screen Size (Diagonal) : 138 cms Minimum</td> </tr> <tr> <td colspan="4">Refresh Rate : 50Hz-100Hz</td> </tr> <tr> <td colspan="4">Make: Sony/ Samsung/ Panasonic/ LG</td> </tr> </table>				Connectivity : 1 x HDMI & 1 x USB				Screen Size (Diagonal) : 138 cms Minimum				Refresh Rate : 50Hz-100Hz				Make: Sony/ Samsung/ Panasonic/ LG																						
Connectivity : 1 x HDMI & 1 x USB																																										
Screen Size (Diagonal) : 138 cms Minimum																																										
Refresh Rate : 50Hz-100Hz																																										
Make: Sony/ Samsung/ Panasonic/ LG																																										
				<p>19.32" LED display</p> <table border="1"> <thead> <tr> <th colspan="3">Minimum specification/ functionality required</th> <th>Compliance</th> <th>Remarks</th> </tr> </thead> <tbody> <tr> <td colspan="3">Type : LED, size 32" (minimum) Professional display</td> <td></td> <td></td> </tr> <tr> <td colspan="3">Display Resolution : 1920 x 1080p (min) (FHD resolution)</td> <td></td> <td></td> </tr> <tr> <td colspan="3">Connectivity : 1 x HDMI & 1 x USB</td> <td></td> <td></td> </tr> <tr> <td colspan="3">Screen Size (Diagonal) : 80 cms Minimum</td> <td></td> <td></td> </tr> <tr> <td colspan="3">Refresh Rate : 50Hz-100Hz</td> <td></td> <td></td> </tr> <tr> <td colspan="3">Make: Sony/ Samsung/ Panasonic/ LG</td> <td></td> <td></td> </tr> </tbody> </table>				Minimum specification/ functionality required			Compliance	Remarks	Type : LED, size 32" (minimum) Professional display					Display Resolution : 1920 x 1080p (min) (FHD resolution)					Connectivity : 1 x HDMI & 1 x USB					Screen Size (Diagonal) : 80 cms Minimum					Refresh Rate : 50Hz-100Hz					Make: Sony/ Samsung/ Panasonic/ LG				
Minimum specification/ functionality required			Compliance	Remarks																																						
Type : LED, size 32" (minimum) Professional display																																										
Display Resolution : 1920 x 1080p (min) (FHD resolution)																																										
Connectivity : 1 x HDMI & 1 x USB																																										
Screen Size (Diagonal) : 80 cms Minimum																																										
Refresh Rate : 50Hz-100Hz																																										
Make: Sony/ Samsung/ Panasonic/ LG																																										
				<p>20.UPS</p> <table border="1"> <thead> <tr> <th colspan="3">Minimum specification/ functionality required</th> <th>Compliance</th> <th>Remarks</th> </tr> </thead> <tbody> <tr> <td colspan="3">Design : Online UPS (2KVA) with batteries</td> <td></td> <td></td> </tr> </tbody> </table>				Minimum specification/ functionality required			Compliance	Remarks	Design : Online UPS (2KVA) with batteries																													
Minimum specification/ functionality required			Compliance	Remarks																																						
Design : Online UPS (2KVA) with batteries																																										

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment			
				Full Load Backup Time : Min. 60 minutes			
				A.C Incoming supply 160-270 V, Single Phase,50 Hz +/-2.5 Hz.			
				During intermittent interruption Cycle Continuously supplying power			
				Make: DB/ APC/ Microtek/ TataLibert			
				21. Network Switch			
				Minimum specification/ functionality required		Compliance	Remarks
				Ports	16 Gigabit Ports, 4 SFP slots, 4 PoE/PoE+ Ports		
				VLANs	255		
				VLAN IDs	1-4096		
				MAC table size	8K		
				Console Port	RS232		
				Operating temperature	-40° C to +85° C		
				Humidity	5 to 95% (non-condensing)		
				MTBF	> 2,00,000 hours		
				Power requirements	24 V DC, redundant dual inputs		

S. No.	RFP volume and clause	Existing clause	Change type (New/ Modify/ Delete)	Revised clause/ Amendment					
				Management tools	Web based, Telnet, CLI management, RMON, Port mirroring				
				Security	ACL, SSH, SSL, MAC based port security, VLAN, RADIUS, TACACS+, SNMP				
				Protocols	HTTP, HTTPS, TFTP, SFTP, SNMP, IGMP				
				Industrial protocols	EtherNet/IP, Modbus/TCP, Profinetv2				
				Redundancy protocol	STP, RSTP, MSTP, Link Aggregation				
				Protection	IP 40				
				Mounting	DIN-rail/ Panel/ Rack				
				IPv6 support and features	Should support IPv6 based configurations				
					IPv6 addressing				
					Ping, Traceroute, VTY, SSH, TFTP, SNMP, HTTP, HTTPS				
					Access Control Lists				
				Minimum L2 features for the L2 switches	Support following Ethernet Standards : 802.3, 802.3x (flow control), 802.3ad (LACP), 802.1p, 802.1q				
					Support loop avoidance mechanism like 802.1d (spanning-tree), 802.1s (MSTP), 802.1w(RSTP), PVST or PVST+				
					Should have mechanism to detect the failures of uplink port				

S. No.	RFP volume and clause	Existing clause	Change type (New/ Modify/ Delete)	Revised clause/ Amendment				
					Support Per port enabling/disabling of unknown unicast/ multicast flooding			
					Support Layer 2 Multicast Features like IGMPv1, v2 and v3			
					Should have REP or equivalent as ring convergence mechanism			
				Minimum L3 features for the L3 switches	Support Static Routing			
					Support Inter Vlan Routing			
					Support Routing Protocols like RIPv1/ RIPv2/ OSPF/ EIGRP/ IS-IS/ BGP 4			
					Support Policy Based Routing			
					Support multicast features like PIM Sparse mode(PIM-SM), Dense Mode(PIM-DM), Sparse-Dense Mode			
					The switch should support DHCP with DHCP option 82 for data insertion and pass through			
					Support HSRP or equivalent features			
					Support RIPng/ OSPFv3/ EIGRP for IPv6			
			Make	Hirsehmann/ Cisco/ Ruggedcom/ Garrettcom/ Juniper/ HP/ Extreme networks/ Perle/ Advantech/ Schneider/ Mootek/ Moxa/ Molex				

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment																													
				<p>22. Wireless Network</p> <table border="1" data-bbox="846 510 1982 1383"> <thead> <tr> <th colspan="2" data-bbox="846 510 1720 587">Minimum specification/ functionality required</th> <th data-bbox="1720 510 1848 587">Compliance</th> <th data-bbox="1848 510 1982 587">Remarks</th> </tr> </thead> <tbody> <tr> <td data-bbox="846 587 1086 1383" rowspan="8">Design Specifications</td> <td data-bbox="1086 587 1720 790">The wireless solution shall consist of a number of Wireless devices (including Indoor, Outdoor, Branch and Mesh Access Points) operating as a solid network under a common network management system</td> <td data-bbox="1720 587 1848 790"></td> <td data-bbox="1848 587 1982 790"></td> </tr> <tr> <td data-bbox="1086 790 1720 869">Access point should support 802.11bgn and 802.11an standards</td> <td data-bbox="1720 790 1848 869"></td> <td data-bbox="1848 790 1982 869"></td> </tr> <tr> <td data-bbox="1086 869 1720 986">Access point should support Inbuilt Spectrum analysis feature to troubleshoot and analyze RF problems remotely</td> <td data-bbox="1720 869 1848 986"></td> <td data-bbox="1848 869 1982 986"></td> </tr> <tr> <td data-bbox="1086 986 1720 1104">Access points should support feature to detect, classify and mitigate the non-Wi-Fi interference</td> <td data-bbox="1720 986 1848 1104"></td> <td data-bbox="1848 986 1982 1104"></td> </tr> <tr> <td data-bbox="1086 1104 1720 1222">Access point should support selective beam forming feature to improve performance of legacy 802.11abg clients</td> <td data-bbox="1720 1104 1848 1222"></td> <td data-bbox="1848 1104 1982 1222"></td> </tr> <tr> <td data-bbox="1086 1222 1720 1305">Each Wireless Access Node shall have the following capabilities :</td> <td data-bbox="1720 1222 1848 1305"></td> <td data-bbox="1848 1222 1982 1305"></td> </tr> <tr> <td data-bbox="1086 1305 1720 1383">Wireless access and at least 2 backhauls in separate radios</td> <td data-bbox="1720 1305 1848 1383"></td> <td data-bbox="1848 1305 1982 1383"></td> </tr> </tbody> </table>				Minimum specification/ functionality required		Compliance	Remarks	Design Specifications	The wireless solution shall consist of a number of Wireless devices (including Indoor, Outdoor, Branch and Mesh Access Points) operating as a solid network under a common network management system			Access point should support 802.11bgn and 802.11an standards			Access point should support Inbuilt Spectrum analysis feature to troubleshoot and analyze RF problems remotely			Access points should support feature to detect, classify and mitigate the non-Wi-Fi interference			Access point should support selective beam forming feature to improve performance of legacy 802.11abg clients			Each Wireless Access Node shall have the following capabilities :			Wireless access and at least 2 backhauls in separate radios		
Minimum specification/ functionality required		Compliance	Remarks																														
Design Specifications	The wireless solution shall consist of a number of Wireless devices (including Indoor, Outdoor, Branch and Mesh Access Points) operating as a solid network under a common network management system																																
	Access point should support 802.11bgn and 802.11an standards																																
	Access point should support Inbuilt Spectrum analysis feature to troubleshoot and analyze RF problems remotely																																
	Access points should support feature to detect, classify and mitigate the non-Wi-Fi interference																																
	Access point should support selective beam forming feature to improve performance of legacy 802.11abg clients																																
	Each Wireless Access Node shall have the following capabilities :																																
	Wireless access and at least 2 backhauls in separate radios																																

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment					
					Capability to provide wireless backhaul to a wired LAN				
					The wireless system shall support multiple services like Data, Voice over IP, Video, and Mobility				
					The wireless network should support the following applications: Plant Extension, Cell site Backhaul				
					The network design should minimize the number of fiber/wired Ethernet connections required for backhaul at required throughput level				
					The total wireless system capacity shall increase as more nodes are added				
					The equipment shall support automatic over the air rate adjustment depending on signal strength and link conditions				
					Support Multiple Receiving Antenna on the access side for better Reception				
					In order to allow optimal channel selection, access points shall detect and measure the signal strength of other Access Points in the area				

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment					
					System should support 512 SSID's and the ability to choose at least 16 SSID's per Access points				
					Each access radio shall be capable of supporting different security profiles on a per SSID basis				
					Multiple Authentication Servers should be supported				
					The design should support the centralized architecture with Wireless LAN controller managed Access points				
				Backhaul Specifications	The Wireless Backhaul shall operate in 5Ghz				
					The equipment shall support integrated wireless backhaul with a capability of delivering at least 20 Megabits/ TCP/ IP throughput for user traffic per backhaul link at 1200 feet				
					Support Encrypted and authenticated connectivity between all backhaul components				
					Wireless Access Nodes shall provide a 'wired' interface for connection to local area networks or backhaul of local clients				

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment					
					Wireless access node shall provide Power Over Ethernet through the wired interface to power other equipment				
					The following interface options shall be available;10/100/1000 Ethernet interface 1000 BaseFX single mode fiber interface				
				Management	Support for SNMP version 2 as well as 3				
					Web Graphical User Interface must support HTTPS				
					Support Single management solution for both Indoor and outdoor wireless Networks				
					Support for TACACS+ or RADIUS for authentication of users to the network				
					All management interfaces supported via Access Control Lists				
					The solution supports redundancy / fault tolerance				
					The network management system must scale to support in excess of 1000 managed elements				
					The network management systems must support automatic configuration download to the network elements				

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment				
					Historical alarm information must be archived by the network management system			
					The network management system must be capable maintaining logs for all management activity performed to all components of the mesh network			
					The network management system must support client/server capabilities with separate access levels and defined user portals			
					The network management system must support standard northbound interfaces			
					The network management system must be capable of alarm filtering to the northbound interface			
				Environmental and Electrical Specifications	Outdoor Equipment shall support powering from AC at 110- 240 VAC (50-60Hz) or 56VDC input			
					Equipment shall support POE			
					Equipment shall support pole, wall, and roof mounting options			
					Geographic orientation flexibility – tilt angle for pole, wall, and roof mounting units			

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment				
					The equipment shall support up to 100 MPH sustained winds & 165 MPH wind gusts			
					The Access point shall be IP67 / NEMA4 rated for dust and water ingress			
					The Access point shall be rated for operation over an ambient temperature range of -40 F (-40 C) to +122 F (+ 50 degree Celsius)			
					Power consumption shall be less than 120 Watts meeting all safety specifications			
					Mounting of the unit cannot exceed 24 inches higher than the top of the light pole / structure			
				23. CISF Cabins				
				Minimum specification/ functionality required			Compliance	Remarks
				Features				
				<u>04'X06'X8.5'H</u>				
				TUBELIGHT:1				
				FAN: 1				
				WINDOW:1: 3ftx3ft SERVICE WINDOW/(3ftx3ft)				
				DOOR: 1 (6.5x3ft) WITH SHED (6 Inch)				
				MCB: 1				

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment			
				MainSwitch : 1			
				ELECTRIC POINT: 5 amps. – 2			
				A.C POINT. 1			
				Cooler point ; 1			
				Exhaust fan ; 1			
				LCD/ PC provision;1			
				Chairs - 2			
				Seating space for two officials			
				BASE FRAME: 50x50mm square pipes. & cross members for nesting are used nesting are used 40x80, C'Channel /40x40 square pipes.18mm cement sheet mounted with vinyl flooring.			
				ROOF FRAME : M.S 18swg Corrugated sheet welded with M.S. frame Structure. Top inner ceiling decorated with 9mm particle board.			
				SIDE WALLS: M.S. frame work with square pipes, & wall thickness 50mm.			
				EXTERIOR WALL: 18swg M.S. bended sheet welded on M.S. frame.			
				INTERNAL WALL: 9MM particle board.			
				CORNER POST: Made of specially 50mm x 50mm square pipe.			
				DOOR: Frame work by tubular pipe of 40x20 external wall made by 18swg. M.S sheet & inner wall decorated by 4mm hardener board, with suitable looking arrangement.			

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment			
				INSULATION: 50 mm thick Glass Wool insulation shall be used for selected walls and 25mm thick Glass Wool insulation to be provided for roof.			
				ELECTRICAL: All wiring shall be concealed and shall be pvc insulated copper wires of ISI quality, gauge 1.5sqmm used for light, socket & 4sqmm for main incoming supply, 5amp plug with switches, & overhead light above the door and light.			
				PAINTS: All components are externally painted with single coat of Zinc phosphate & final coat of corrosion free HD paint			
				LEGS : 4 corner legs 4 inch			
				SHADE: 18swg M.S. sheet above the door with a depth of 6"			
				General requirement: Cabin should accommodate 2 persons easily and should be supplied with required furniture like table, Air Condition, lighting, last mile cabling, etc.			
				24.Unified Threat Management Device			
				Minimum specification/ functionality required	Compliance	Remarks	
				Firewall throughput – 1gbps			
				Minimum Concurrent sessions – 40,000			
				New sessions per second – 3000			
				Must be a 64 bit hardware platform			

S. No.	RFP volume and clause	Existing clause	Change type (New/Modify/Delete)	Revised clause/ Amendment			
				Ethernet ports – 05			
				SFP (Mini GBIC) - 02			
				Features:			
				<ul style="list-style-type: none"> - Stateful inspection firewall - Identity based firewall - Intrusion prevention system - Gateway antivirus, antispymware and antispam - Web content filtering, application filtering, web application firewall, VPN - Group based control - Bandwidth management - Inbuilt on-appliance reporting with 250GB internal storage - High availability - Load balance - Monitoring and reporting - All licenses for 07 years - 24X7 support 			
				Certifications – ICSA lab/ IPSec/ Antivirus and Network IPS (Copy of certifications to be submitted)			